

98-AR460 **電氣規格表** **ELECTRONIC SPECIFICATIONS**

機種 MODEL **AR460** 客戶 CUSROMER **PROART**

DESCRIPTIONS / 品名 **Multi-Channel Power Amplifier**

NO	DESCRIPTIONS	TEST CONDITIONS	UNIT	NOM	LIMIT	TEST RECORD
1	POWER OUTPUT *6 Channel 輸出功率	Load	< 1% THD	W	150	>150
		8 Ohms	< 3% THD	W	160	>160
		Load	< 1% THD	W	250	>250
		4 Ohms	< 3% THD	W	280	>280
		Load/Bridged	< 1% THD	W	300	>300
		8 Ohms	< 3% THD	W	350	>350
2	GAIN 總增益		LINE IN	db	30	+/-3
			MIC IN	db		
3	FREQUENCY RESP. 頻率響應	(-1db)	LINE IN	Hz	10-60K	20-40K
			MIC IN	Hz		
4	TONE CONTROL 高低音響控制		BASS	db		
			TREBLE	db		
5	OUTPUT IMPEDANCE 輸出組抗		Ohms	8	4	
			Ohms			
6	INPUT IMPEDANCE 輸入組抗		Ohms	30K	>30K	
			Ohms			
7	NOISE 雜音指數		VR MIN	mv		
			VR MIX	mv	0.1	<0.01
8	T.H.D 總失真度				0.002	<0.005
			1WATT	%		
9	HUM 交流雜音		VR MIN	db		
			VR MIX	db	105	>105

作業及外觀檢點 CHECK ASSY' & PARTS SPECIFICATIONS

1.一般AMPLIFIER標準			

	版本及日期	確認 Approved	製成design
	A/0		

