

A00-AR412		電氣規格表		ELECTRONIC SPECIFICATIONS			
機種 MODEL		AR412		客戶 CUSROMER		PROART	
DESCRIPTIONS / 品名				HI-END Power Amplifier			
NO	DESCRIPTIONS	TEST CONDITIONS		UNIT	NOM	LIMIT	TEST RECORD
1	POWER OUTPUT 輸出功率	Load	< 1% THD	W	550	>550	
		8 Ohms	< 3% THD	W	600	>600	
		Load	< 1% THD	W	950	>950	
		4 Ohms	< 3% THD	W	1000	>1000	
		Load/Bridged	< 1% THD	W			
	8 Ohms	< 10% THD	W				
2	GAIN 總增益		LINE IN	db	25	+/-3	
			MIC IN	db			
3	FREQUENCY RESP 頻率響應	(-1db)	LINE IN	Hz	10-60K	15-50K	
			MIC IN	Hz			
4	TONE CONTROL 高低音響控制		BASS	db			
			TREBLE	db			
5	OUTPUT IMPEDANCE 輸出組抗			Ohms	4/8		
				Ohms			
6	INPUT IMPEDANCE 輸入組抗			Ohms	30K	>30K	
				Ohms			
7	NOISE 雜音指數		VR MIN	mv			
			VR MIX	mv	0.05	<0.1	
8	T.H.D 總失真度				0.005	<0.005	
			1WATT	%			
9	HUM 交流雜音		VR MIN	db			
			VR MIX	db	105	>105	
作業及外觀檢點 CHECK ASSY' & PARTS SPECIFICATIONS							
1.一般AMPLIFIER標準							
		版本及日期		確認		製成	
		A/0					